

MOBILE LED PROJECTOR ML750





PALM-SIZED PROJECTION POWERHOUSE


































Present your best wherever you go with the ultra-compact Optoma ML750 portable LED projector. The power and performance of a full sized projector on the palm of your hand.

Delivering an impressive 700 ANSI lumens and 10,000:1 contrast ratio, with razor sharp focus and magnificent color accuracy. The Optoma ML750 will make your presentations more impactful than ever before.

Designed for traveling professionals, the palm-sized Optoma ML750 weighs less than one pound. Has built-in Media player and Office Viewer for completely PC-Free presentations. HDMI and MHL connectivity for direct from mobile device presentations. Its LED light source is rated to last over 20,000 hours so you can present with confidence. Never a bulb to buy or replace.

CONNECTIVITY (May require optional accessories)























DIGITAL

Apple TV[®]

MOBILE LED PROJECTOR — ML750

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	Single 0.45″ DMD DLP® Technology by Texas Instruments™
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	VGA: WSXGA+ (1680 x 1050) HDMI: HD 1920 x 1080
Brightness	700 Lumens
Contrast Ratio	10,000:1 (full on/full off)
Displayable Colors	16.7 Million
Light Source Life and Type	20,000+ hours LED
Projection Method	Front, rear, ceiling mount, table top
Keystone Correction	±40° Vertical, auto keystone correction
Uniformity	>85%
Offset	100%
Aspect Ratio	16:10 Native, 16:9 and 4:3 compatible
Throw Ratio (distance/Width)	1.5 (distance/width)
Projection Distance	1.8'-10.6' (0.55- 3.23 m)
Image Size (Diagonal)	17"-100" (0.43-2.54 m)
Projection Lens	F=2.0, f=14.95 mm
Digital Zoom	1.7x
Audio	One 1-Watt speaker
Noise Level (Normal/Bright)	30dB
Remote Control	IR remote control
Operating Temperature	41-104°F (5-40°C), 85% max humidity
Power Supply	AC Input 100–240V, 50–60Hz, auto-switching DC output: 19v/3.2A, 65W
Power Consumption	Max 62W, <0.5W (standby)
Memory	1.5GB Onboard memory, microSD slot supports up to 32GB

COMPATIBILITY SPECIFICATIONS

Computer Compatibility	WSXGA+, SXGA+, WXGA+, WXGA, SXGA, XGA, SVGA, VGA resized, VESA, PC and Macintosh compatible	
Video Input Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)	
3D Compatibility*	120Hz frame sequential 3D for resolutions up to XGA, 60Hz field sequential 3D for resolutions up to 480i. Not compatible with 3DXL.	
Vertical Scan Rate	50-120Hz	
Horizontal Scan Rate	15-100kHz	
User Controls	Complete on-screen menu, adjustments in 16 languages	
Image file compatibility	.jpg, .bmp	
Office file compatibility	PowerPoint, Word, Excel, .pdf	
Music file compatibility	.mp3, .wma, .ogg, .adpcm-wav, .pcm-wav, .aac	
Video file compatibility	.avi, .mkv, .divx, .ts, .dat, .vob, .mpg, .mpeg, .mov, .mp4, .rm, .rmvb, .wmv	
I/O Connection Ports	24-pin universal port (VGA), HDMI, microSD, USB-A	

PHYSICAL SPECIFICATIONS

Security	Kensington® Lock Port
Weight	Projector: 14.1 oz Power adaptor: 5.1 oz
Dimensions (W x H x D)	4.1" x 1.5" x 4.2" (104 x 38 x 107 mm)



Kensington Lock Port

ML750, I/O cable (VGA & composite input), carrying case, AC power cable, power adapter, remote control, batteries, quick start user manual

Accessories

Wi-Fi adapter: WUSB

Remote (replacement): BR-ML75N

AC power adapter (replacement): BC-ML55PDX AC power cord (replacement): BC-PUPNXY02

Universal to VGA/audio cable (replacement): BC-PK5AVGX

Carrying case (replacement): BK-ML70S

UPC 796435 41 903 5



